

# The AA4400X series of Bottled Water Coolers



## New HygieneGuard Tap Cover

The most critical hygiene area is undoubtedly the tap, which often gets contaminated through user hand contact (by comparison the "waterside" is much less critical). A silver impregnated plastic tap cover is designed to stop bacterial growth from contact contamination. The HygieneGuard tap cover can easily be replaced.

#### Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish

## **Drip Tray**

Lift out design which can be connected to mains drainage, High impact durable plastic. Removable anti splash grid

## **Taps**

Modern push and hold solenoid taps replace the old fashioned manual taps. The push and hold action prevents leaving the tap running by mistake whilst operating as a safety tap mechanism at the same time. The spouts of the solenoid taps are protected by the new HygieneGuard tap covers. Their silver impregnation is designed to prevent hand to tap bacterial contamination

## **Cup Holder**

Integrated cup holder with exposed locking nuts to open up for easy refilling of cups

# **Removable Lower Front Panel**

Spring loaded lower front panel. Remove drip tray and simply press down to remove entire lower front panel for easy access.

## The AASIP4400X model

This model comes with SIP Ozonation which automatically sanitises the Cooler for 5 minutes at 2am every 24 hours trough a burst of Ozone into the water tank and system. SIP Ozonation has been thoroughly tested and it has been accepted that it reduces the need for hard sanitisation of Coolers by half (POU Coolers from 2 x to 1 x per year and Bottled Coolers from 4 x to 2 x per year). SIP Ozonation represents a significant advance over UV and other sanitising methods

## **Refrigeration System**

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload. Unit hermetically sealed. R-134a refrigerant

## **Cooling System**

Stainless Steel 3 litre cold water tank. Thermostatically controlled to 4C - 12C

## **Heating System**

Stainless Steel 2 litre tank. Thermostatically controlled to between 87 and 92°C.

Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of the Cooler

## **Power Supply**

220 Volt, 50/60 Hz. Provided with a 3 pin plug and 180 cm power cord

## **Dimensions**

Difficusions		
Floor Standing:	Height	1165mm
Car Ell.	Width	340mm
12-191 11	Depth	340mm
Table Top:	Height	488mm
	Width	340mm
	Depth	340mm

# **Shipping Weights**

Floor Standing:	18kg
Table Top:	15kg

# **Anthracite Finish:**

CONKIT 3300XP

WCBC 4400X	Floor Standing, Cook & Cold
WCBH 4400X	Floor Standing, Hot & Cold
WCBTC 4400X	Table Top, Cook & Cold
WCBTH 4400X	Table Top, Hot & Cold
WCBCSIP4400X	SIP Self Sanitising, Floor Standing, Cook
	& Cold
WCBHSIP4400X	SIP Self Sanitising, Floor Standing,
	Hot & Cold

# Your Local Distributor is









Conversion Kit to Point of Use

